



Rugged, flexible combination DMX control and low voltage power cable.

Specifications		
Conductors	Data pair: 22 AWG [0.34 mm ²] Tinned, annealed copper stranded 19 x 34	Power: 14 AWG [2.5 mm ²] Tinned, annealed copper stranded 41 x 30
Insulation	80° C, 300 Volt PVC	
	Data pair: Nom. wall: 0.012" [0.30 mm] Min. wall: 0.008" [0.20 mm]	Power: Nom. wall: 0.012" [0.30 mm] Min. wall: 0.009 [0.23 mm]
Color Code	Data pair: Red/Green	Power: Black/White
Assembly	Power singles cabled around shielded data pair w/drain wire	
Shield	Aluminum / mylar around 22 AWG pair, aluminum in, 100% coverage	
Drain	22 AWG [0.34 mm ²] Tinned, annealed copper stranded 19 x 34	
Jacket	Black PVC Nom. wall: 0.040" [1 mm] Elongation: 300% Tensile strength: 2,000 psi UV and fungus resistant	
Legend	PROPLEX *PCCCT* POWERDATA LOW VOLTAGE CABLE 14 AWG 2/C + 22 AWG 1 PAIR CL2 (UL) E177741 FT1, UV RESISTANT INSTALLATION CABLE	
Physical	Outside diameter: 0.290" [7.37 mm] nom. Weight: 73 lbs. per 1,000 ft. [104 Kg/Km]	
Temperature	Plus 90° C, minus 20° C	
Conductivity	Data pair: 15.5 Ohms (max.) per 1,000 ft @ 20° C	Power: 2.75 Ohms per 1,000 ft @ 20° C nom.
Characteristic Impedance	Data pair: 60 Ohms	
Capacitance	Data pair: 25pf nom. cond.-to-cond, 44pf nom. cond.-to-shield	

RoHS
Compliant

Worldwide Exclusive Distribution



sales@tmb.com

Los Angeles
+1 818.899.8818

London
+44 (0)20.8574.9700

tmb
www.tmb.com

New York
+1 201.896.8600

Beijing
+86 10.8492.1587

Toronto
+1 519.538.0888