

ProPlex® IQ Series Two

IQ Two 1616 – 16-way Bidirectional DMX-Ethernet Node



- Assign 16 DMX Connectors to up to 16 ArtNet/sACN universes
- Input or output on any connector
- Full RDM functionality
- Merge Artnet or Streaming ACN from multiple sources
- RDM Manager software available for system setup and feedback
- Web interface – manage large networks locally or remotely
- Large touchscreen for quick, easy setup and operation
- Rugged, tour-ready ProPlex “Blue Box” RackMount chassis

BUILT FOR THE ROAD!
DATA DISTRIBUTION YOU CAN DEPEND ON.

ProPlex®
DATA DISTRIBUTION

Worldwide Exclusive Distribution

Innovative, Performance-Driven Show Technology Since 1983

tmb.com

Los Angeles

London

New York

Beijing

Toronto

+1 818-899-8818

+44 (0)20-8574-9700

+1 201-896-8600

+86 10-8492-1587

+1 519-538-0888



Technical Specifications	
Part Number	PPIQB161615RD
Ethernet Ports	1
ArtNet/sACN Universes	16 max.
DMX Ports	16
DMX Connectors	Neutrik XLR5 Female
DMX Port Isolation	Optical, up to 1000V
Ethernet Connector	Neutrik EtherCON RJ45
Network Protocols	ArtNet, sACN (E1.31)
Power	100-240V, 50-60 Hz
Operating Temp.	-20° to +40° C
Unit Dimensions (WxHxD)	19 x 3.5 x 8 in (483 x 90 x 205 mm)
Unit Weight	8.5 lb (3.8 kg)
Shipping Dimensions (WxHxD)	21 x 7.3 x 16 in (533 x 185 x 406 mm)
Shipping Weight	10.5 lb (4.8 kg)

IQ Two 1616 Network Example

