

# ProPlex® IQ Series Two

## IQ Two 416, 16-way DMX-Ethernet Node/Opto-Splitter



16 DMX outputs with RDM that can be easily assigned to 4 ArtNet/sACN universes. RDM enabled and in combination with RDM manager software can be used for fixture system setup and maintenance. Unit configuration can be done locally or remotely – using touchscreen, built-in web server, or with dedicated PC application.

“It’s like a 4-port Node with 4 universes of opto-splitting over 16 ports all in one box!”

- Assign 4 ArtNet/sACN universes to 16 DMX outputs.
- Full RDM functionality.
- RDM Manager software available for system setup and feedback.
- Web interface – manage large networks locally or remotely.
- Large touchscreen for quick, easy setup and operation.
- Rugged, tour-ready ProPlex “Blue Box” RackMount chassis.

**BUILT FOR THE ROAD!**  
DATA DISTRIBUTION YOU CAN DEPEND ON

**ProPlex®**  
DATA DISTRIBUTION

Worldwide Exclusive Distribution

Innovative, Performance-Driven Show Technology Since 1983

tmb.com

Los Angeles

London

New York

Beijing

Toronto

+1 818-899-8818

+44 (0)20-8574-9700

+1 201-896-8600

+86 10-8492-1587

+1 519-538-0888



<b>Technical Specifications</b>	
Part Number	PPIQB41615RD
Ethernet Ports	1
ArtNet/sACN Universes	4
DMX Ports	16
DMX Connectors	Neutrik XLR5 Female
DMX Port Isolation	Optical, up to 1000V
Ethernet Connector	Neutrik EtherCON RJ45
Network Protocols	ArtNet, sACN (E1.31)
Power	100-240V, 50-60 Hz
Operating Temp.	-20° to +40° C
Unit Dimensions (WxHxD)	19 x 3.5 x 8 in (483 x 90 x 205 mm)
Unit Weight (unpacked)	7.3 lbs (3.3 kg)