



# Nuri\*Lite

Way Better Than Darkness!

## \* Highball

RGBW + Amber + UV PAR



- Versatile 30° beam angle for many applications
- Compact and lightweight housing
- High output
- Double yokes for floor or truss mounting
- Flicker-free operation
- Specially selected LEDs for rich, intense colors
- “6 in 1” LEDs with in-lens color mixing
- Includes power cable. Available accessories include Nuri\*Filters, a detachable top hat, barndoor, and Wireless Solution™ W-DMX receiver.

The Highball combines superior RGBWAUV color mixing with adjustable beam widths via the proprietary Nuri\*Filter System. Specially selected, high-quality LEDs provide deep, saturated colors with outstanding white balance and exceptionally smooth projection. Flicker-free operation makes the Highball suitable for TV, film, and theatre, as well as corporate events. Nuri\*Filters allow the user to adjust beam shape and angle by inserting unique, proprietary optional filters, including an elliptical filter! The unique shape of the Highball keeps cables clear of sightlines.

The fixture has double yokes for floor or truss mounting. An LCD display provides quick and easy-to-read access to all settings, including different dimmer curves. Controlled by DMX, the Highball features extensive color temperature control and a pre-programmed FX engine. The Highball comes with 5-pin XLR and PowerCon connectors. Available accessories include a detachable top hat, barndoor, and built-in Wireless Solution™ W-DMX receiver option. The Highball is the perfect choice for the most discerning professionals.



Innovative, Performance-Driven Show Technology Since 1983

tmb.com

Los Angeles

London

New York

Beijing

Toronto

+1 818-899-8818

+44 (0)20-8574-9700

+1 201-896-8600

+86 10-8492-1587

+1 519-538-0888



## SPECIFICATIONS

Part Number	NUR156170
DMX channels	6, 8 or 12
Beam angle	30° (adjustable with Nuri*Filter System, see Accessories)
Power supply	100-240 VAC, 50-60 Hz
Power consumption	105 Watt Max.
Cooling	Low noise regulated fan
Power Connection	PowerCon in & thru
DMX connection	5-pin XLR in & thru
Dimensions (HxWxD)	11.93 x 10.12 x 8.11" [303 x 257 x 206 mm]
Shipping dimensions	12.4 x 10.4 x 14.2" [315 x 265 x 360 mm]
Weight	12.13 lb. [5.5 kg]
Shipping weight	14.55 lb. [6.6 kg]
Certification	CE, RoHS
IP rating	IP22
Included items	Power cable
Accessories	Top Hat, Barndoor, W-DMX receiver card, 39.1° Nuri*Filter, 55.9° Nuri*Filter, 65° Nuri*Filter, 83.8° Nuri*Filter, 65° x 25° Nuri*Filter (elliptical)

