



# Nuri\*Lite

## Way Better Than Darkness!

## \* Manhattan

### Indoor/Outdoor RGBW LED Wash

- Four individually controllable segments
- 21° beam angle
- Deep, saturated colors
- Flicker free operation
- Rugged, road-ready chassis
- IP65 rating for temporary production use, not intended for permanent outdoor installation
- Includes power cable, barndoor, filter holder, and Wireless Solution™ W-DMX receiver. Nuri\*Filters available separately.



The Manhattan is an extremely powerful IP65-rated LED wash fixture, perfect for illuminating large walls or other surfaces, indoors and outdoors. Ultra-bright with an extraordinarily even field make it a true LED alternative for traditional wash lights at a fraction of energy cost. Thirty-six calibrated, high-power RGBW LEDs are arrayed in a handy 9x4 rectangular configuration, divided into four individually-controlled horizontal sections.

The Manhattan boasts a punchy 21° beam angle which can be easily adapted to other beam angles, even elliptical via optional Nuri\*Filters. The unique LED Boost Mode offers 140% output when using two colors simultaneously. The Manhattan comes with an intelligent cooling system and variable fan control, making it ideal for TV, theatre, and other noise-critical applications.

The Manhattan comes standard with filter frame, barndoor, and Wireless Solution™ W-DMX receiver onboard, but can also be connected with 5-pin XLR connectors. Power is connected through a PowerCon TRUE1 connector.



Innovative, Performance-Driven Show Technology Since 1983

tmb.com

Los Angeles

London

New York

Beijing

Toronto

+1 818-899-8818

+44 (0)20-8574-9700

+1 201-896-8600

+86 10-8492-1587

+1 519-538-0888



## SPECIFICATIONS

Part Number	NUR156220
DMX channels	4-30
Beam angle	21° (adjustable with Nuri*Filter System, see Accessories)
Power supply	100-240 VAC, 50-60 Hz
Power consumption	360 Watt Max.
Cooling	Active Intelligent cooling system
Power connection	PowerCon TRUE1 in & thru
DMX connection	W-DMX wireless, 5-pin XLR in & thru
Dimensions (HxWxD)	13.4 x 19.5 x 5" [340 x 495 x 125 mm]
Dimensions (with stand) (HxWxD)	15.3 x 19.5 x 10" [388 x 495 x 255 mm]
Shipping dimensions	23.2 x 19 x 12.7" [590 x 483 x 323 mm]
Weight	28 lb. [12.7 kg]
Shipping weight	41.9 lb. [19 kg]
Certification	CE, RoHS
IP rating	IP65 (rating for temporary production use, not intended for permanent outdoor installation)
Included items	Power cable, barndoor, filter holder, stand, W-DMX Card
Accessories	36.6° Nuri*Filter 63.6° Nuri*Filter 82.7° Nuri*Filter 21° x 63.6° (elliptical) Nuri*Filter 63.6° x 21° (elliptical) Nuri*Filter 92° x 63.6° (elliptical) Nuri*Filter

