

SOLARIS™

Introducing the
Incredible

FLARE™JR



Available with
((()))
Wireless Option


Powered By
CREE LEDs

Little brother of the fabulous
Solaris LED Flare, winner
Live Design 2013 Product
of the Year and PLASA 2013
Sustainability Award



Super Bright LED RGBW Wash/Strobe/Blinder

KASMEI Filter Holder!



MORE SAVINGS! Simultaneous color wash and strobe in ONE fixture – Saves labor, time, space, energy, and cost.

MORE SMOOTH! Instantaneous RGBW color mixing with 1200Hz refresh rate – Smooth on-camera dimming.

MORE VERSATILE! Pixel-map feature divides into 1, 2, or 4 sections for ultimate control.

MORE SATURATED COLORS! Intense, deep reds and blues. Ultra-bright greens. Brilliant camera-friendly whites.

MORE FLEXIBLE! 36-degree beam angle optimized for most applications.

Innovative, Performance-Driven Show Technology Since 1983

tmb.com

Los Angeles
+1 818-899-8818

London
+44 (0)20-8574-9700

New York
+1 201-896-8600

Beijing
+86 10-8492-1587

Toronto
+1 519-538-0888



FLARIE[®]JR

SPECIFICATIONS

Light sources	32 10W CREE [®] LEDs (divided in to 4 pixels)
Beam spread	36°
Colors	4- R, G, B, W
Average color wavelength (manufacturer rated)	Red: 625 nm
	Green: 530 nm
	Blue: 460 nm
	White: >5700K
Refresh rate	1200 Hz
Intensity control	16-bit or 8-bit
Control	DMX-512
Wireless control	Wireless option available by special order
AC power	90-277 VAC universal input, 50/60 Hz
Cooling	Air-cooled fan
Operating temperature	-20°C - +40°C
DMX channels	3-24 depending on control mode
DMX connectors	In/Out - XLR 5-pin F/M
Max. power draw	~400 W
Power connectors	In- PowerCon 20A blue + THRU- PowerCon grey
Fixing	Adjustable yoke
Fixture body	Powdercoated steel
Unit dimensions (HxWxD)	6.1 x 13.4 x 5.3 in (15.5 x 34 x 13.5 cm)
Shipping dimensions (HxWxD)	TBA
Unit weight	10.6 lb (4.8 kg)
Shipping weight	12 lb (5.4 kg)

Specifications and features are subject to change without notice.

