

STAR CABLE®

Microphone Cables

Economical, Professional-Grade Mic Cables

2 conductors 24 AWG stranded bare copper, polypropylene insulated, overall serve shielded, PVC jacketed microphone cable.



Available fully assembled in retail packaging with Neutrik® or generic XLR connectors.



| SPECIFICATIONS | | |
|----------------|--------------------------|---|
| Part number | | WDPMIC24 |
| Conductor | AWG Size and Stranding | 24 AWG 16 strands 36 AWG |
| | Material | Bare annealed copper |
| Insulation | Material | Polypropylene |
| | Wall Thickness | 0.013" nom. |
| | Diameter | 0.050" +/- 0.002" |
| | Color Code | Blue paired with red |
| Assembly | Lay Length | 1 3/4" maximum left hand |
| | Fillers | Jute as required |
| Shield | Material | Bare annealed copper serve |
| | Coverage | 95% nom. |
| Jacket | Material | Matte black finish polyvinyl chloride |
| | Wall Thickness | 0.055" nom. |
| | Diameter | 0.230" +/- 0.005" |
| Markings | Type | Surface printing in white ink (blue on white jacket) |
| | Legend | STARCABLE WDPMIC24 24 AWG PROFESSIONAL LOW CAPACITANCE 1 PAIR MICROPHONE CABLE |
| Electrical | Capacitance | 21 pF/ft @ 1 kHz Between Conductors |
| | | 37 pF/ft @ 1 kHz Conductor to Shield |
| | Characteristic Impedance | 70 ohms @ 1 MHz |
| Physical | Resistance | 23 ohms/1000 ft. at 20°C |
| | Weight | 31 lbs. per 1000' |
| Stock Length | | 5000' plywood spool |

RoHS
Compliant

Innovative, Performance-Driven Show Technology Since 1983

tmb.com

Los Angeles

London

New York

Beijing

Toronto

+1 818-899-8818

+44 (0)20-8574-9700

+1 201-896-8600

+86 10-8492-1587

+1 519-538-0888

